



SIM908

SIM908 module is a complete Quad-Band GSM/GPRS module which combines GPS technology for satellite navigation. The compact design which integrated GPRS and GPS in a SMT package will significantly save both time and costs for customers to develop GPS enabled applications.

Featuring an industry-standard interface and GPS function, it allows variable assets to be tracked seamlessly at any location and anytime with signal coverage.

Smart Machine Smart Decision

General features

- Quad-Band 850/900/1800/1900MHz
- GPRS multi-slot class 10
- GPRS mobile station class B
- Compliant to GSM phase 2/2+
 - Class 4 (2 W @ 850/900 MHz)
 - Class 1 (1 W @ 1800/1900MHz)
- Control via AT commands (GSM 07.07 ,07.05 and SIMCom enhanced AT Commands)
- SIM application toolkit
- Supply voltage range:
 - GPRS: 3.2 ~ 4.8 V
 - GPS: 3.0 ~ 4.5V
- Low power consumption
- Dimensions: 30*30*3.2mm
- Weight:
 - SIM908:5.2g
 - SIM908-C:11.1g
- Operation temperature:
 - 40 ° C to +85 ° C

Specifications for SMS via GSM / GPRS

- Point-to-point MO and MT
- SMS cell broadcast
- Text and PDU mode

Specifications for audio

- Tricodec
 - Half rate (HR)
 - Full rate (FR)
 - Enhanced Full rate (EFR)
- Hands-free operation
- Echo cancellation

Specifications for data transfer

- GPRS class 8/10: max. 85.6 kbps (downlink)
- PBCC support
- Coding schemes CS 1, 2, 3, 4
- CSD up to 14.4 kbps
- USSD
- Non transparent mode
- PPP-stack
- Integrated TCP/IP stack

Compatibility

- AT cellular command interface

Specification for GPS

- Receiver type
 - 42-channel
 - GPS L1 C/A code,
 - High-performance STE engine
- Sensitivity
 - Tracking: -160 dBm
 - Cold starts : -143 dBm
- Time-To-First-Fix
 - Cold starts: 30s (typ.)
 - Hot starts: 1s (typ.)
- Accuracy
 - Horizontal position : <2.5m CEP
- Power consumption (GSM engine in idle mode)
 - Acquisition 77mA
 - Tracking 76mA

Interfaces

- 80-pad with SMT type
- Interface to external SIM 3V/ 1.8V
- Dual analog audio interfaces
- SPI interface
- RTC backup
- Charge interface
- A serial interface and a debug interface for GSM/GPRS
- Debug interface for GPS NMEA information output
- Two separate antenna connectors for GSM/GPRS&GPS

Certifications

- CE
- ROHS